

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

JC979 U.S. PTO

09/843987



Intyg Certificate



Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) *Sökande* *Siemens-Elema AB, Solna SE*
Applicant (s)

(21) *Patentansökningsnummer* *0001999-2*
Patent application number

(86) *Ingivningsdatum* *2000-05-29*
Date of filing

Stockholm, 2001-02-13

För Patent- och registreringsverket
For the Patent- and Registration Office


Hjordis Segerlund

Avgift
Fee *170.-*

**PATENT- OCH
REGISTRERINGSVERKET
SWEDEN**

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

Description

Interface Unit for an Electrophysiology Measurement System

The present invention relates to an interface unit for use in an electrophysiology measurement system.

5 Electrophysiological measurement systems generally comprise a monitoring system for one or more of receiving, storing, processing and displaying signals from a number of patient interactive elements such as catheter mounted intracardiac electrodes, surface ECG electrodes, blood parameter sensors,
10 and like physiological parameter sensors; and an interface unit. The monitoring system often includes a switching unit by which measurements may be selectively made using different combinations of intracardiac electrode signals.

The interface unit is typically provided bedside to receive
15 the proximal ends of wires which are connected at their distal ends to the patient interactive elements and provide for their electrical connection in an optional manner to the switching unit of the monitoring system. The wires are received by the interface unit in releasable engagement with
20 input terminals which for the intracardiac electrodes are often arranged at the outer surface of the unit in a grid fashion, or so as to receive a multi-pin connector of a particular catheter. An output socket or permanent lead is provided for electrical connection to a connector in the
25 monitoring system and comprises contacts connected to and arranged in a fixed correspondence with the input terminals. Which electrode wire connects to which terminal is dependent largely on the combination of catheters being used for a particular electrophysiology study, the nature of that study
30 and how the monitoring system is configured to receive the electrical signals.

The monitoring system may actually be provided with connectors for several interface units. Each connector then establishes electrical channels for signals from an

associated interface unit by which the signals are passed to a corresponding amplifier board where they are amplified and otherwise conditioned before they are operated on by the switching unit.

- 5 Before undertaking any electrophysiology study the measurement system must be initially set-up so that the correct catheter wires are mated with the correct terminals on the interface unit so that the correct measurements are made during the study. To facilitate this set-up it is known
- 10 to provide an interface unit wherein each terminal is permanently labelled in numerical sequence for identification purposes. Each wire of a particular catheter is usually provided with an identifying label by the manufacturer. Look-up tables can be constructed using these two sets of labels
- 15 to indicate the wire/terminal mating configuration required for a particular study. A wipe-clean surface may be available on the interface unit so that a label can be provided for each terminal used in the study which identifies the catheter electrode wire to be inserted according to the look-up table.
- 20 A problem may occur with the known electrophysiology measurement system when attempting to check if the correct wire is connected to the correct connector for a particular electrophysiology measurement study. This is compounded by the fact that the monitoring system and the interface unit
- 25 are often situated some distance apart and linked through a 'maze' of wires.

- To alleviate this problem it is known to provide an electrophysiology measurement system in which the monitoring system identifies itself to the interface unit. This is done
- 30 by arranging for the monitoring system to generate an identifier on the interface unit, for example by lighting a coloured diode or providing an alphanumeric code, which corresponds to an identifier for the connector to which the interface unit is connected. The user can then determine
- 35 which unit is connected to which connector by a simple visual

inspection of the identifier generated on the interface unit but not if the correct unit is connected to a connector. However, this solution does not readily assist the user in identifying whether or not the correct labels are provided on the correct interface unit.

Additionally, during at least the initial set-up of the monitoring system the wire/input terminal mating configuration of the interface unit necessary for a particular electrophysiology study must be entered manually into the system and the correspondence checked with the actual configuration provided by the interface unit. This procedure often involves two personnel, one at the interface unit and one at the monitoring system, one announcing the desired configuration to the other who then either establishes the correct wire/terminal connection or enters the information into the monitoring system. This procedure typically needs to be repeated every time the electrophysiology study is varied and provides an opportunity for user input error which at best can cause errors in the data analysis and at worst can cause injury to the patient.

According to the present invention there is provided an interface unit as described in and characterised by the present claim 1. By providing a unit which can generate an output signal containing information which can, for example, identify either or both the housing and a label layer (if provided) to an electrophysiology monitoring system or provide set-up protocols for use by the system then an automatic determination of the correct connections for a desired electrophysiology study can be made automatically by the system and the potential for errors during a set-up procedure can at least be reduced.

Preferably, the interface unit may comprise a removable label layer selectable from a library of label layers having a visible indication of a particular wire/connector mating configuration permanently fixed at a surface thereof together

with an element, such as a bar code label, useable to generate the output signal particular to the layer. This enables catheter wire connections to be rapidly established and varied whilst automatically providing information identifying the connections when the element is read by an appropriate reader, such as a conventional bar code reader.

Usefully, the interface unit may provide the output signal which identifies to the electrophysiology monitoring system the electrophysiology study to be performed, for example by generating a coded reference to the study or by generating a protocol useable to configure signal switches within the monitoring system in order to carry out the study. This further automates the set-up procedure and thereby reduces the potential for user input error.

Exemplary embodiments of the present invention will now be described with reference to the drawings of the accompanying figures, of which:

Fig. 1 shows a representation of a first embodiment of an interface unit according to the present invention;

Fig. 2 shows a representation of a second embodiment of an interface unit according to the present invention;

Fig. 3 shows a representation of a third embodiment of an interface unit according to the present invention;

Fig. 4 shows a block diagram illustrating an electrophysiology measurement system according to the present invention; and

Fig. 5 shows an automatically generated visual representation of interface unit/layer configuration for a desired electrophysiology study.

Considering now Fig. 1, an interface unit 2 comprises a housing 4 and a label layer 6 removably located at an outer surface 8 of the housing 4 and is selectable from a library

of different label layers 10,12, all of which are releasably attached to the housing 4 by means of binding posts 14. A plurality of female connectors 16 are arranged grid-wise in the surface 8 for releasable mating with male connectors which terminate sensor wires of a combination of catheters used in a particular electrophysiology study (not shown) and register with through-holes 18 in a label layer 6,10,12 when the layer 6,10,12 is properly located on the surface 8 of the housing 4.

10 A fixed indication showing how the sensor wires of each catheter from the catheter combination is to be mated with the female connectors 16 is provided on each label layer 6,10,12. As illustrated in Fig. 1 for the removably located label layer 6 this indication may comprise catheter labels 20
15 a,b ("RA","RV"); linear demarcations 22 a,b,c which group together those holes 18 (hence female connectors 16) which are intended to receive the wires belonging to an individual catheter of the combination; and for each of the individual catheter groupings 22 a,b,c labels 24 a,b,c associating the
20 sensor wires of that catheter with the holes 18 (or connectors 16). By visibly grouping together the connectors 16 of a particular catheter in this way the wire label convention (d,2,3...) normally used by a catheter manufacturer can be transferred to the label layers 6,10,12 with a reduced
25 risk of confusion between different catheters. The label layers 6,10,12 also carry a human readable label layer identification code 26 to uniquely identify each label layer 6,10,12 and hence a particular catheter combination.

Thus, as an example for the embodiment of Fig. 1, it will be
30 readily determined that for the currently located label layer 6 - identified as "A1" - an electrophysiology study may be carried out using any combination of the three catheters identified on the layer 6. It can be seen from this example that a first catheter, placed in the Right Atrium "RA",
35 carries twelve sensor wires identified by the manufacturer with labels "d" to "12" which will mate with the twelve holes

connected by the appropriate line 22a; a second, placed in the Right Ventricle "RV", carries four sensor wires identified by the manufacturer with labels "d" to "4" and will mate with the four holes connected by the appropriate line 22b; and a third, placed elsewhere in the heart (no catheter identifier label being yet provided), carries eleven sensor wires identified by the manufacturer with labels "d" to "11" will mate with the eleven holes connected by the appropriate line 22c.

10 A printed circuit board (PCB) 28 is contained within the housing 4 and carries on it, amongst other things, a signal generator comprising a read-only-memory (ROM) 30, for example an (electrically) erasable-programmable ROM ((E)EPROM), which has its output connected to a pin 32 of a "D-type" connector 15 34, as illustrated by means of connecting line 36 in Fig. 1. Other pins, shown generally at 38, connect to an edge connector (not shown) on the PCB 28 which connects individual pins to individual female connectors 16 in a fixed relationship. The number of pins 38 may actually be less than 20 the number of female connectors 16 if, for example, conventional signal multiplexing circuitry is included within the housing 4 so as to "connect" in a fixed manner individual connectors 16 to one or more pins 38.

25 This D-type connector 34 can readily be replaced by a permanent lead hard-wired to the PCB 28.

The ROM 30 is configured on the PCB 28 to provide an output signal containing information particular to the housing 4 at the pin 32 for receipt by an electrophysiology monitoring system (see Fig. 3). The information may, for example, 30 comprise an identifier code particular to the housing 4 and which has a correspondence to a human readable housing identification code 40, if present. It will be apparent to those skilled in the art that if the interface unit 2 is modified so that the removable label layer 6 is permanently 35 located on the surface 8 of the housing 2 (with the need for,

amongst other things, the binding posts 14 and additional layers 10,12 being removed) the signal provided by the ROM 30 will equally translate as information particular to the now fixed label layer 6 and hence to a unique catheter wire/connector combination provided by the unit 2.

It will be appreciated by those skilled in the art that the ROM 30, has a capacity to carry amounts of information in excess of a simple identification code and the information can comprise information useable by an electrophysiology monitoring system to automate its set-up. Such information can include a protocol for the wire/connector mating configuration which may then be used within an electrophysiology monitoring system to establish an appropriate switching configuration in order to achieve desired lead combinations or to select particular catheters necessary for a desired electrophysiology study from the combination of catheters shown on the label layer 6.

A second embodiment of an interface unit 42 according to the present invention is shown in Fig. 2 in which components common to this unit 42 and that unit 2 of Fig. 1 are identified by the same reference numerals. The interface unit 42 comprises a housing 4 and a plurality of label layers 6,10,12 which are each removably locatable on an outer surface 8 of the housing 4, as described with respect to the unit 2 of Fig. 1. Each layer 6,10,12 has, in addition or as an alternative to a human readable layer identification code 26, a machine readable code carrying element, here shown as a bar code element 44 particular to the label layer 6,10,12. A bar code reader 46 is connected via a signal cable 48 to a dedicated processing circuit 50 which is located on a PCB 28 within the housing 4 and which operates to convert the optical signal produced by the reader 46 from the code element 44 to an electrical signal. This electrical signal can then be passed from the unit 2 via a pin 32 of a D-type connector (or lead wire of a hard-wired lead) to an electrophysiology monitoring system (see Fig. 4) where it

uniquely identifies to the system the label layer 6 on the surface 8 of the housing 4 and which has a correspondence to the human readable layer identification code 26, if present.

5 As illustrated in Fig. 2, the interface unit 42 may also be provided with a ROM 30, such as described above with respect to Fig. 1, on the PCB 28 which provides the electrophysiology monitoring system with information particular to the housing 4, such as an identification code which has a correspondence to a human readable housing identification code 40, if present.
10

A third embodiment of an interface unit 52 according to the present invention is shown in Fig. 3 in which components common to this unit 42 and those units 2, 42 of Figs. 1 and 2 are identified by the same reference numerals. The interface unit 52 comprises a housing 54 and a label layer 56, selected from a plurality of label layers (not shown) dependent on a particular electrophysiology study to be performed. The layer 56 has a plurality of through holes 18 which correspond to a plurality of electrical connectors 16 when the layer 56 is correctly located at an outer surface 58 of the housing 54.
15 20 To facilitate the correct location and to help retain the layer 56 on the surface 58 guides 60 may be provided which, in co-operation with the surface 58, establish channels within which edges of the layer 56 are to be received.

25 A ROM 62, such as an EEPROM, is located together with associated circuitry on the label layer 56 and contains information particular to the label layer 56. This information can include items which range from, for example, a layer identification code to protocols used to control the operation of an electrophysiology monitoring system to perform a particular electrophysiology study associated with the layer 56 and/or to present collected data in a particular manner.
30

A reading head 64 is located on the outer surface 58 of the housing 54 to establish electrical contact with the ROM 62 when the layer 56 is correctly located on the surface 58 and is connected to reading circuitry 66 located within the housing 54. The ROM 62, head 64 and associated circuitry 66 co-operate in a manner substantially similar to conventional "smart-card" technology to provide an output signal which contains the information stored in the ROM 62. It will be appreciated that other smart-card communication technology such as a wireless telemetry arrangement or a magnetic reader may be substituted for the electrical arrangement described above to provide for information communication between the label layer 56 and the housing 54.

External access to this output signal and to any sensor signals present at the connectors 16 is provided via a permanently connected lead 68.

A holder 70 is provided integral with the housing 54 in which label layers which are not used in the particular electrophysiology study may be slidably retained.

An embodiment of an electrophysiology measurement system 72 according to the present invention is shown in Fig. 4. The electrophysiology measurement system 72 comprises an electrophysiology monitoring system 74 and one or more (here four) interface units 2 of the present invention, each of which is connected to catheter mounted sensors 76 required for a particular electrophysiology study. Each interface unit 2 has a different label layer 6,10,12 (see for example Fig. 1) at its outer surface and so each provides a different catheter wire/connector mating configuration.

The electrophysiology monitoring system 74 comprises a monitoring unit 78 which can receive information input from each of the interface units 2 as well as from a user interface device 80 such as a keyboard and can send information to a hospital information system HIS as well as

to a presentation device such as a visual display unit 82 and a printer 84.

More particularly, the monitoring unit 78 here comprises an array of conditioning units 86, each of which may be
5 connected to a one of the interface units 2 by means of a dedicated externally accessible input socket having input connectors (not shown) corresponding to the pins 32, 38 of the D-connector 34 of a unit 2 and internal signal channels 88. The internal signal channels 88 could even be replaced by
10 a single multiplexed connection to a single or to multiple conditioning units 86.

Signals from sensors 76 connected to a particular interface unit 2 pass to the inter-connected conditioning unit 86 within the monitoring unit 78 where it is amplified and
15 otherwise conditioned, for example by filtering, before it is passed to a switching unit 90. A suitably programmed microprocessor 92 operates to configure the switching unit 90 so as to selectively switch signals from all of the connected interface units 2 and combine them to produce so-called
20 electrophysiology lead signals necessary to a particular electrophysiology study. Information required by the microprocessor 92 in order to correctly configure the switching unit 90 for the particular electrophysiology study may be provided to the microprocessor 92 via the user input
25 device 80 or additionally or alternatively via information passed from the signal generator 30 of the interface unit 2 as the output signal particular to the unit 2.

It will be appreciated by a person skilled in the art that an embodiment of the present invention having the functionality
30 of some or all of the individual components which comprise the monitoring unit 78 incorporated into the microprocessor 92 may be readily constructed whilst remaining within the scope of the invention as claimed.

These lead signals from the switching unit 90 can then be processed and analysed within the microprocessor 92 in a manner dependent on the electrophysiology study, as is well known in the art.

- 5 Additionally or alternatively the signal generator 30 may be adapted to provide an output which identifies the particular housing 4 in which it is contained. In the unit 2 of Fig. 1 the label layer 6 which is located on an outer surface 8 of the unit housing 4 is selectable from a library of label
10 layers 6,10,12 according to a desired electrophysiology study to be undertaken (which may be identified to the microprocessor 92 by the user through the user interface device 80) and is identified by a human readable layer identification code 26. In this case the microprocessor 92
15 may be set-up by a user to retain in a memory a list of all layer identification codes; a list of those codes which identify label layers necessary for different electrophysiology studies; and a list linking the signal output by a particular identification means with the human
20 readable housing identification code 40 of the particular housing. If it is necessary that a particular sensor signal combination appears at a particular conditioning unit 86 a list linking the conditioning unit 64 and the label layer necessary to provide the combination can also be retained in
25 the memory of the microprocessor 68.

- When the signal from a signal generator 30 of each of the one or more connected interface units 2 is received at an inter-connected conditioning units 86 it is passed to the microprocessor 92 together with a code identifying the
30 particular conditioning unit 86 receiving the signal. The microprocessor 92 is programmed to then construct a look-up table which links the human readable box identification code 40 with a human readable layer identification code 26 necessary to provide the sensor signal combination from the
35 identified interface unit 2 which is required at the inter-connected conditioning unit 86 in order to carry out the

desired electrophysiology study. This look-up table 94 (see Fig. 4) may be presented on one or both of the display 82 and the printer 84 for use by a user to very simply manually verify that the correct label layer 6 is located on the correct interface unit 2 through a comparison of the visible layer code and box identification code combinations on the interface unit 2 with those presented in the table 94. Alternatively or additionally each interface unit 2 may be provided with a display (not shown) which can be accessed and programmed by the microprocessor 92 of the monitoring unit 78 to present on the housing 4 the layer identification code corresponding to the code 26 of the necessary layer 6 for that unit 2.

If, as mentioned above with respect to Fig. 1, the label layer 6 is permanently located on the housing 4 of the interface unit then the output generated by the signal generator 30 also inherently identifies the label layer 6 and hence the associated wire/connector mating configuration. In this case the microprocessor 92 may be programmed to produce a sensible warning signal if the correct interface unit 2 is not connected to the correct conditioning unit 86 (dependent on the interface/conditioning unit combination required for the user indicated physiological study) or is missing.

Alternatively, the microprocessor 92 may be programmed to select the switch combination within the switching unit 90 dependent on the correct interface units 2 being present for the desired electrophysiology study, irrespective of how the conditioning units 86 inter-connect with the interface units 2.

The electrophysiology measurement system 72 of Fig. 3 may be modified by substituting the interface units 2 of Fig. 1 with interface units 42 or 52 of Figs. 2 and 3 respectively. In this case the signal generator 44,46,50; 62,64,66 provides signals to the monitoring system 74 particular to the label layer 6;56 of each connected unit 42;52. The microprocessor

92 of the monitoring unit 78 may then be programmed to produce a sensible warning signal if the correct label layer 6 is not provided on an interface unit 42;52 connected to the correct conditioning unit 86 (dependent on the interface/conditioning unit combination required for the user indicated physiological study) or is missing.

The microprocessor 92 may be programmed to select the switch combination within the switching unit 90 dependent on the correct label layers 6;56 being present for the desired electrophysiology study, irrespective of how the conditioning units 86 inter-connect with the interface units 42;52. Indeed the signal generator 44,46,50; 62,64,66 may be adapted to provide a switching protocol to the microprocessor 92 which is then used to establish the correct combination.

Furthermore, the switch combinations may also be established so that particular catheters from the connected catheters are selected to achieve the correct catheter combination necessary for a particular electrophysiology study. Indeed the microprocessor 92 may be additionally or alternatively configured to set the switch combination of the switching unit 86 to carry out a particular electrophysiology study which is identified to the microprocessor 92 by the label layer specific information output from the signal generator 44,46,50; 62,64,66. In this manner the electrophysiology monitoring system 74 can be rapidly re-configured to perform any desired electrophysiology study simply by varying the label layers 6;56 located on one or more of the connected interface units 42;52 and thereby vary the label layer specific information provided to the system 74. The use of appropriate layer specific information from the signal generator 44,46,50; 62,64,66 to control the set-up of the monitoring system 74 reduces the amount of human input data and thus the opportunity for data entry errors.

It will be appreciated by those skilled in the art that the microprocessor 92 may be programmed to modify the operation

of the electrophysiology monitoring system 74 in many other ways dependent on the information received from the signal generator 44,46,50; 62,64,66 of each connected interface unit 42;52. The system 74 may, for example adapt the type and
5 layout of information it records (either digitally on a digital storage medium or visually using a printer or visual display unit) in response to set-up protocols received from the signal generator 44,46,50; 62,64,66.

Although the embodiments of the electrophysiology measurement
10 system presented above are described on the basis of a plurality interface units, all being of the same type, an electrophysiology measurement system having only one interface unit or a combination of interface unit types according to the present invention connected to the
15 electrophysiology monitoring system within which the microprocessor is adapted to respond accordingly will remain within the scope of the invention as claimed.

0
1
2
3
4
5
6
7
8
9

Claims

1. An interface unit (2;42;52) comprising a plurality of externally accessible electrical connectors (16), each connector (16) for releasably mating with a one of a plurality of wires from a combination of catheter mounted sensors (70); and means (38;68) adapted to provide a fixed coupling to the plurality of connectors (16) and couplable to an electrophysiology monitoring system (54) characterised in that the unit (2;42;52) further comprises a signal generator (30;44,46,50;62,64,66) adapted to generate an output signal comprising information particular to and originating from the unit(2;42;52) for use by the system (54).
2. An interface unit as claimed in Claim 1 characterised in that the unit comprises a housing (4) and in that the signal generator (30) is adapted to generate the output signal comprising information particular to the housing (4).
3. An interface unit as claimed in Claim 2 characterised in that the signal generator comprises an element having a read only memory (30) adapted to carry the information particular to the housing.
4. An interface unit as claimed in any preceding claim characterised in that the unit (42;52) further comprises a label layer (6;10;12;56) for providing at an outer surface (8;58) a visible indication (20a,b,22a,b,c,24a,b,c) of a wire/connector mating configuration; and in that the signal generator (44,46,50;62,64,66) is adapted to generate the output signal comprising information particular to the layer (6;10;12;56).

5. An interface unit as claimed in Claim 4 characterised in that the label layer (6;10;12;56) is removably locatable on the outer surface (8;58).
- 5 6. An interface unit as claimed in claim 5 characterised in that the label layer (6;10;12;58) is configured with the visible indication (20a,b,22a,b,c,24a,b,c) permanently fixed at a surface thereof.
- 10 7. An interface unit as claimed in Claim 5 or Claim 6 characterised in that the signal generator (44,46,50;62,64,66) comprises an element (44;62) co-located with the layer (6;56) and adapted to carry machine readable information particular to the layer (6;56) and means
15 (46,50;64;66) adapted to co-operate with the element (44;62) to read the information and generate the output signal representative thereof.
8. An interface unit as claimed in any preceding claim characterised in that the signal generator
20 (30;44,46,50;62,64,66) is adapted to generate the output signal providing a protocol for the wire/connector mating configuration.
9. An interface unit as claimed in any preceding claim characterised in that the signal generator
25 (30;44,46,50;62,64,66) is adapted generate the output signal providing at least part of an electrophysiology study set-up protocol.
10. An electrophysiology measurement system (72) comprising an electrophysiology monitoring system (74) and one or more
30 interface units (2;42;52) for establishing in an optional manner an electrical coupling of wires from a plurality of catheter mounted sensors (76) with the monitoring system (74) characterised in that each of the one or more interface units (2;42;52) consists of a unit as claimed in

any of the previous claims and in that the monitoring system (74) is adapted to receive the output from the signal generator (30;44,46,50; 62,64,66) of each of the one or more units (2;42;52) and to modify its operation dependent thereon.

11. An electrophysiology measurement system (72) as claimed in Claim 10 characterised in that each of the one or more interface units (2;42) comprises a removably locatable label layer (6;10;12) provided with a surface having permanently fixed thereon the visible indication (20a,b,22a,b,c,24a,b,c) of a different wire/connector mating configuration together with a human readable label layer identification code (26); a housing (4) provided with a human readable housing identification code (40); and signal generator (30) adapted to generate the output signal particular to the housing (4); and in that the electrophysiology monitoring system (74) comprises a data presentation device (82;84) and a processor means (92) having stored therein label layer identification codes for predetermined electrophysiology studies; the processor means (92) being adapted to modify the operation of the electrophysiology monitoring system (74) to present on the presentation device (82;84) a layer identification code/housing identification code protocol (94) for a selected one of the predetermined electrophysiology studies.

12. An electrophysiology measurement system (72) as claimed in Claim 10 characterised in that each of the one or more interface units (2;42) comprises a removably locatable label layer (6;10;12); in that the signal generator (44,46,50;62,64,66) of each of the one or more interface units (42;52) is adapted to generate the output signal particular to the label layer (6;10;12;56) and in that the electrophysiology monitoring system (74) comprises a processor means (92) having stored therein an indication of label layer or layers required for each of a plurality of predetermined electrophysiology studies and is adapted to

compare the one or more label layers (6;10;12;56) identified from the output signal with the indication for a selected electrophysiology study and to modify its operation dependent on the comparison.

5 13. An electrophysiology measurement system (72) as claimed in Claim 10 characterised in that each signal generator (44,46,50;62,64,66) is adapted to generate the output signal providing at least part of an electrophysiology study set-up protocol and in that the electrophysiology
10 monitoring system (74) comprises a processor means (92) adapted to receive the set-up protocol and to modify the operation of the system (74) to facilitate the performance of the electrophysiology study.

14. An electrophysiology measurement system (72) as claimed
15 in Claim 13 characterised in that the electrophysiology monitoring system (74) comprises a signal switching unit (90) having switch settings controllable by the processor means (92) and in that the set-up protocol comprises information for use by the processor means (92) to
20 vary the switch settings dependent on the electrophysiology study.

15. An electrophysiology measurement system as claimed in Claim 13 or 14 characterised in that set-up protocol comprises information for use by the processor means
25 (92) to vary one or both of presentation format and type of study data recorded by the monitoring system (74).




Abstract

Interface Unit for an Electrophysiology Measurement System

An interface unit (2) comprises a plurality of externally accessible electrical connectors (16), each connector (16) for releasably mating with a one of a plurality of wires from a combination of catheter mounted sensors. A fixed configuration connector (38) is provided in a fixed coupling to the plurality of connectors (16) and is couplable to an electrophysiology monitoring system. The unit (2) further comprises a signal generator, such as a suitably programmed EEPROM (30) in combination with appropriate electrical circuitry mounted on an internally located printed circuit board (28), adapted to generate an output signal comprising information particular to and originating from the unit(2) for use by the electrophysiology monitoring system.

Fig. 1







Fig. 1

2/5

Fig. 2

3/5




Fig. 3

4/5




Fig. 4

5/5

SETUP		ID
<u>UNIT</u>	<u>LABEL</u>	
BOX 1	A1	
BOX 2	A2	
BOX 3	A3	
BOX 4	A4	

94

Fig. 5